


Geberit Mapress Copper T-piece, reduced



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water $\leq 120^\circ\text{C}$
- For service water and process water
- For compressed air (oil purity class 0–3)
- For negative pressure

- For inert gases (e.g. nitrogen)
- For industrial gases (e.g. acetylene, shielding gases)
- For technical building systems, industry and shipbuilding

- Seal ring made of EPDM, black, from $\varnothing > 54\text{ mm}$
- Pressing socket with transparent protection plug

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of CIIR, black, up to $\varnothing \leq 54\text{ mm}$

TECHNICAL DATA

| | |
|------------------|--------------------------------|
| Product material | Cu-DHP copper CW024A (EN 1412) |
|------------------|--------------------------------|

| Art. no. | DN | d, \varnothing mm | d1, \varnothing mm | d2, \varnothing mm | arc $^\circ$ | L cm | L1 cm | l cm | l2 cm | Z cm | Z1 cm | Z2 cm |
|----------|---------|---------------------|----------------------|----------------------|--------------|------|-------|------|-------|------|-------|-------|
| 61256 | 20 / 12 | 22 | 15 | 22 | 90 | 7.4 | 3.8 | 3.7 | 3.7 | 1.6 | 1.8 | 1.6 |