

SL150 NON-ELECTRIC WATER SOFTENER - STANDARD

EAN	5027639900100
Product code	900100
People	Up to 5
Height	470mm
Depth	483mm
Depth (With Connectors)	540mm
Width	240mm
Approximate regeneration time	12 Minutes
Resin volume	3.3 Litre (Ultra Fine)
Salt used per regeneration	330gm
Water used per regeneration	18 Litre
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Includes	2 x Standard 15mm Hoses
Hi-Flo option	Code 900131
Power Source	None (Water Pressure)
Installation Orientation	Left / Right / Rear
Maximum Ambient Temperature	40°C
Maximum / Minimum Working Pressure	6 bar Max / 1 bar Minimum
Maximum Soft Water (at 200 ppm)	750 Litres
Maximum Soft Water (at 300 ppm)	500 Litres
What salt to use	Granular, Tablet or Block
Warranty	5 Years parts 2 Years Labour*



Simple
'Click-Connect'
Installation

*** IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.

TECHNICAL HELPLINE 01785 811636