

### SL TWIN ELECTRIC TWIN TANK WATER SOFTENER

EAN	5027639900261
Product code	900261
People	Up to 6 people
Height	460mm
Depth	465mm
Depth (With Connectors)	490mm
Width	260mm
Approximate regeneration time	45 Minutes
Resin volume	3.5 Litre x 2
Salt used per regeneration	525 Grams
Water used per regeneration	37 Litre
Average regeneration schedule	
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2" BSP
Hi-Flo option	
Power Source	240v 50hz mains transformer
Installation Orientation	
Maximum Ambient Temperature	40°C
Maximum / Minimum Working Pressure	6 bar Max / 1 bar Minimum
Maximum Soft Water (at 200 ppm)	2 x 870 Litre
Maximum Soft Water (at 300ppm)	2 x 600 Litres
What salt to use	Tablet
Warranty	5 Years parts 2 Years Labour*



#### Requires one of the following installation kits

<b>900803</b>	15mm Standard Installation Kit
<b>900858</b>	22mm Hi-Flow Hoses x 2
<b>900827</b>	Combi installation Kit
<b>900810</b>	22mmHi-Flow Installation Kit

**\* IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.

TECHNICAL HELPLINE 01785 811636