

### SL-S SINGLE TANK NON-ELECTRIC WATER SOFTENER

EAN	5027639900292
Product code	9002292
People	Up to 4
Height	492mm
Depth	475mm
Depth (With Connectors)	500mm
Width	235mm
Approximate regeneration time	12 Minutes
Resin volume	4.5 Litre
Salt used per regeneration	340gm
Water used per regeneration	25 Litre
Flow Rate @ 1 bar Pressure Drop	1800 Litres / Hour
Flow Rate @ 2 bar Pressure Drop	2400 Litres / Hour
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Installation Orientation	Rear Only
Minimum/Maximum Operating Temp	2° - 23°C
Minimum/Maximum Working Pressure	1.5 bar Max / 6 bar Minimum*
<b>* Pressure Reducing Valve Must Be Fitted Over 6 bar</b>	
What salt to use	Tablet or Block
Warranty	5 Years parts 2 Years Labour*

TECHNICAL HELPLINE 01785 811636



#### Requires one of the following installation kits

<b>900803</b>	15mm Standard Installation Kit
<b>900858</b>	22mm Hi-Flow Hoses x 2
<b>900827</b>	Combi installation Kit
<b>900810</b>	22mmHi-Flow Installation Kit

**\* IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.

Hardness Level	100	125	150	200	250	350	525
Litres Between Regeneration	1358	1083	905	689	531	394	256