SAF ES SMBAS BB

SAFFRON Tap Range Saffron Eco start Small Basin Mixer Brushed Brass



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Loop			
Connection Inlet:	1/2" BSP Flexible Tails			
Connection Outlet:	M24 Coin Slot 5lpm Aerator			
Number of Tap Holes:	1			
Valve/Cartridge Type:	28mm Cold Start Upper Seal Cartridge			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.5 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Features:

- Eco Start technology saves energy by having cold water as the default central start position of the tap handle. Hot water is only activated when the tap lever is moved from the central position, so your boiler is not unnecessarily fired up.
- This tap has a flow regulator, which limits the flow of water to 5 litres per minute, reducing the amount of water you use.
- Long life ceramic cartridge for added durability and smooth control.
- Everything you need in the box including flexible tails and clicker waste so nothing to buy separately.
- On-trend brushed brass finish to make a statement in your bathroom
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in chrome and black.
- Co-ordinating Bathroom taps and Recess shower available.

Product Certifications:



Dimensions (measure	ements in mm)
H 13.	
<u> </u>	<u>U</u>
135	
	90
<u> </u>	<u>↓</u>
45	

Flow Rates (I/min)							
System Pressure (bar)	0.5	1	2	3	5		
SAF ES SMBAS BB (mixed)	2.5	3.5	4.5	4.8	5.1		

TECHNICAL DATA SHEET





Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.