SAI BAS C

SAIL Tap Range Sail Basin Mixer Chrome



_			
_	\sim	*11	ires:
	Ca	uu	II CO.

- Long life ceramic cartridge for added durability and ease of use
- Metal fixing nut for added durability
- Flexible tails included
- Includes clicker waste

Specification					
Product Type:	Taps				
Main Construction Material:	Brass				
Mount Type:	Deck Mounted				
Handle Type:	Lever Handle				
Connection Inlet:	M10 x 15mm Flexible Tails				
Connection Outlet:	M24 5lpm Flow Limiter				
Number of Tap Holes:	1				
Valve/Cartridge Type:	35mm Ceramic Cartridge				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2 bar				
Maximum Dynamic Pressure (bar):	5.0 bar				
Maximum Hot Water Temperature °C:	65°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single Flow				
Isolation Included:	No				

Dimensions (measurements in mm)





For more products, visit our website: http://www.bristan.com



135	50	
94 61	47	GI 1/4"

Flow Rates (I/min)									
System Pressure (bar)	0.2	0.5	1	2	3	5			
SAI BAS C (mixed)	5	5	5	5	5	5			

TECHNICAL DATA SHEET



