Product information

Instaflow



Instantaneous 5.4kW Single Point Water Heater



A compact designed unit, great for underbasin installations as a space saving option and ideal for handwashing. It will provide instantaneous hot water on demand to a single outlet.

- Heats the water when it starts to flow through for an economical hot water solution as no power is used when in standby operation
- Power selection is smooth and easy for optimum settings selection
- Suitable for a single hand basin
- IPX4 splashproof rated
- · Can be used with manual mixer taps

Product Code: 5.4kW: SPINSF05SW



Power ratings	5.4kW (at 240V)
Finish	White
Visual indicators	Power-on
Water connection	1/2"BSP
Terminal block	5.4kW - 6mm max cable
Water supply	Mains cold water
Water pressure min	0.4bar
Water pressure max	6 bar
Activation point	2l/min
Power setting	Variable - temperature determined by flow and incoming water temp

Flow Rates	Winter	Spring/Autum	Summer	
	(Incoming Water Temp 5°C)	(Incoming Water Temp 12°C)	(Incoming Water Temp 20°C)	
	5.4kW	5.4kW	5.4kW	
3.0 l/min	31°C	38°C	46°C	
4.0 l/min	24°C	31℃	39°C	
6.0 l/min	18°C	25°C	33℃	

Product information

Instaflow



See you first thing Britain

Instantaneous 7.7kW & 10.1kW Multi Point Water Heater



Instaflow 7.7kW & 10.1kW is a multipoint instantaneous water heater. The Instaflow multipoint instantaneous water heater is available in two kilowatt ratings to suit any needs. This wall mounted unit can be used for 1 or 2 outlets in a property.

- Heats the water when it starts to flow through for an economical hot water solution as no power is used when in standby operation
- Suitable for 1 outlet or 2 outlets in a property, for example 1 kitchen sink or 2 hand basins
- Power selection is smooth and continuous for optimum settings selection

Product Code:

7.7kW: SPINSF07MW **10.1kW:** SPINSF10MW



Power ratings	7.7kW & 10.1kW (at 240V)
Finish	White
Visual indicators	Power-on
Water connection	1/2"BSP
Terminal block	10mm max cable
Water supply	Mains cold water
Water pressure min	0.6bar
Water pressure max	6 bar
Activation point	2.7l/min
Power setting	Variable - temperature determined by flow and incoming water temp

Flow Rates			Spring/Autum			
	(Incoming Water Temp 5°C)		(Incoming Water Temp 12°C)		(Incoming Water Temp 20°C)	
	7.7kW	10.1kW	7.7kW	10.1kW	7.7kW	10.1kW
3.0 l/min	42°C	53°C	49°C	60°C	57°C	68°C
4.0 l/min	33°C	41°C	40°C	48°C	48°C	56°C
6.0 l/min	23°C	29°C	30°C	36°C	38°C	44°C