

Product Code: 32930WH Friction Hinged Support Rail 800mm with Concealed Fix

Stainless Steel

White Polyester



Product Code 32930WH

Friction Hinged Support Rail 800mm with Concealed Fix

Backplate

Stainless steel, 143mm in depth x 103mm in width complete with 4 fixing holes. Specification 304 S15 2B to BSEN 10088-2 1985, 0.2mm in thickness. Mig welded with stainless steel wire – spec ER308LSi 1.6mm diameter.

Tubing Material

35mm diameter stainless steel tubing x 1.20 (18g) welded tubing – A151 304 Annealed

Coating

Hot Cleaner to remove oil and surface preservatives, phosphated to seal surface. White Polyester powder coated, electrostatically 15 microns in thickness. RAL9016

Weight Loading

BS8300 2009 loading up to 120kgs in horizontal drop weight position and at 45 degree position.

<u>Maintenance</u>

Non required but would suggest periodic cleaning with anti-bacterial cloths, avoid abrasive /corrosive cleaners as they may damage the coated surface.

Fixings

Not supplied

<u>Colours</u>

Also available in most RAL Colours

Net Weight

4kgs - Fixings not supplied

IMPORTANT: Bathex recommend our products are installed by experienced, skilled crafts people. Fixings not supplied.