



Maximo Water Softener



Model: GS6000 HE Code: GS6004HE

Operation: Meter control with Opti-brining **Dimensions:** 1100H x 350W x 565D

Connections: 3/4" male

Optional Rapid-Fit Bypass to go into pipework to GS6000 HE

Model: Rapid Fit bypass

Code: MBP00134 for 34'' male bsp Code: MBP00144 for 1'' male bsp

Model: GS4000 HE Code: GS4004HE

Operation: Meter control with Opti-brining **Dimensions:** 870H x 350W x 565D

Connections: 34" male

Optional Rapid-Fit Bypass to go into pipework to GS4000 HE

Model: Rapid Fit bypass

Code: MBP00134 for 3/4" male bsp Code: MBP00144 for 1" male bsp



8 reasons to use Maximo...

- ✓ Up to 6430 litres per regen at 300ppm (4595 ltrs/GS400HE)
- ✓ Intelligent microprocessor that controls, monitors and remembers your water use
- ✓ High flow rates (up to 75 lpm) and low pressure drops
- ✓ Opti-brining as standard up to 56% salt savings
- ✓ Suitable for up to 28mm supplies
- ✓ Proven long life and accurate metering system
- √ 7 year parts and 2 years labour guarantee
- ✓ Comes complete with pair of Maxflow connection hoses and 3mtrs of drain/overflow hose

Model	Litres of solvent-free resin	Salt use per regeneration (kg)	Capacity per regeneration@300ppm	Flow rates Ipm
GS6000HE	35	3.7 - 5.3	6430 litres	75
GS4000HE	25	2.6 - 3.7	4595 litres	75