KEY FEATURES

- 3kW Incoloy immersions fitted as standard
- Titanium immersion options available on request.
- Compression connections supplied as standard
- White plastic-coated wipe clean rigid case for premium appearance.
- Pre plugged secondary tapping for ease of installation.
- All connections clearly labelled
- Butt welded process used throughout
- Robotically welded
- Branded quality components

TECHNICAL **SPECIFICATION**

Product Code	TRSMVD 0090LFC	TRSMVD 0120LFB	TRSMVD 0150LFB	TRSMVD 0170LFB	TRSMVD 0210LFC	TRSMVD 0250LFC	TRSMVD 0300LFC
Cylinder Capacity (L)	**90**	**120**	**150**	**170**	**210**	**250**	**300**
Height (A)	720	900	1100	1280	1470	1720	1980
Diameter (B)	545	545	545	545	545	545	545
Weight (Empty)	21kg	26kg	33kg	38kg	41kg	46kg	55kg
Weight (Full)	111kg	146kg	183kg	218kg	251kg	296kg	355kg
Standing Loss (kwh)	0.96	1.11	1.26	1.40	1.48	1.76	2.03
Energy Efficiency Class	C	C	C	C	C	C	C
Energy Efficiency (nwh%)	36	39	37	37	37	38	38
ErP Usage (kWH/day)	6.330	6.885	7.306	12.985	13.055	20.510	20.880