

Hot Water Outlet

Secondary Return
(210L and above)

Temperature & Pressure Relief
Valve

Cold Inlet Feed

Boiler Flow

Stat Pocket

Boiler Return



KEY FEATURES

- Single high recovery coil
- 3kW Incoloy immersion fitted as standard
- Titanium immersion options available on request.
- Compression connections supplied as standard
- Bevelled stat pocket for better fitting
- White plastic-coated wipe clean rigid case for premium appearance.
- Pre plugged secondary tapping for ease of installation.
- All connections clearly labelled
- Butt welded process used throughout
- Robotically welded
- Branded quality components
- Smooth tube coil construction for durability and performance

TECHNICAL SPECIFICATION

Product Code	TRSMVI 0090LFC	TRSMVI 0120LFB	TRSMVI 0150LFB	TRSMVI 0180LFB	TRSMVI 0210LFC	TRSMVI 0250LFC	TRSMVI 0300LFC
Cylinder Capacity (L)	87	117	147	176	206	246	296
Height (A)	720	900	1100	1280	1470	1720	1980
Diameter (B)	545	545	545	545	545	545	545
Weight (Empty)	23kg	30kg	38kg	42kg	45kg	51kg	60kg
Weight (Full)	109.39kg	146.39kg	184.39kg	217.86kg	248.25kg	296.25kg	355.25kg
Standing Loss (kwh)	0.96	1.11	1.26	1.40	1.48	1.76	2.03
Energy Efficiency Class	B	B	B	B	B	C	C
Reheat Indirect (Min)	14.3	19.05	23.71	29.20	32.5	38.83	43.80